

15WK

Insulated and
Non-Insulated EnviroDuct®

APPLICATIONS

- Portable heater ducting with moderately high heat content

FEATURES

- Used in both blowing and exhausting applications
- Excellent UV stabilization with mold and mildew inhibitors for rigorous outdoor use
- Flame resistant in accordance with UL94VTM-O

This product is not recommended for aircraft ground support applications.

EnviroDuct® is a registered trademark of ABC Industries, Inc.



ENVIRODUCT®

Thermoplastic Elastomer with Warp Knit Backer, Steel Wire Helix, Sewn Construction

SPECIFICATIONS

Weight	15 oz./yd. ² (509 g/m ²)	
Temperature	-65° to 350° (-54° to 177° C) Intermittent	
Standard Pitch	Pitch	Diameter
	3" (7.5 cm) 4" (10 cm)	6" & 7" (150 & 200 mm) 8" (200 mm) or Larger
Expanded Pitch	7" (18 cm)	12" (300 mm) or Larger
Wire	Hard-Drawn Steel	
Inside Diameter	6" - 36" (150 - 900 mm) Larger diameters available upon request.	
Length	15', 25' (4.5, 7.5 m)	
Color	Black, Desert Tan, Olive Drab, White, Yellow	
Optional Wearstrip	Heavy-Duty Black (Military Spec) and White	
Optional End Finishes	Pinlock Coupling, Belt Cuff, Wire Rope Coupling, Soft Cuff	



ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077

800.426.0921 Toll-Free

574.267.5166 Phone

574.267.2045 Fax

sales@abc-industries.net

www.abc-industries.net



Registered to
ISO 9001