

150 KW INDUSTRIAL AIR HEATER

Unit Performance / Data



General

Manufacturer Unit Model Number Equipment Insurance Value Duct Connections Custom Air Products & Services, Inc. PHUH-0NN-150KE0NN-GE5-0-VUP \$43,500.00 1 x 20" Supply Air & 1 x 20" Return Air

Dimensions

Length (Base)	96" (8')
Width	50" (4'2")
Height w Casters	55 1/4" (4'-7")
Height w/o Casters	50 5/8" (4'-2")
Unit Weight	2,500 Lbs.

Electrical

Single Point Power Supply Connections

Heating MCA Heating MOCP 480V / 3PH / 60HZ 4 Cam-Lok connectors


205 250

			Heating
CFM	TSP	MOTOR HP	neating
8,000	5.00	10	




150 KW INDUSTRIAL AIR HEATER

Unit Pictures / Drawings



Supply Air View with **Dimensional Data**

Galvanized Skid & Cage



www.customairproducts.com (713) 460-9009



One (1) 20" Return Air with Casters & Hot Dipped Galvanized Skid & Cage Industrial Heater Control Panel with Dimensional Data Product Data

ATER One (1) 20" Supply Air with Casters

150 kW Industrial Air Heater Features:

- Four (4) stages of heating capacity control
- Heater High-Medium-Low capacity selector switch
 - High (all four (4) stages) =150 kW
 - Medium (three (3) stages) =112.50 kW
 - Low (two (2) stages) =75 kW
- 8,000 CFM high static plenum fan rated at 5.00 TSP
- 10 HP, 3600 RPM motor, TEFC
- VFD air volume control
- Direct drive plenum fan
- Unit capable of 300 F leaving air temperature
- Easy access panels for efficient serviceability
- Heavy duty skid, forklift slots, tie-downs. Hot dipped galvanized skid & cage
- 1" Thermax cabinet insulation
- Coated Lifting / Stacking cage
- Rugged design built for rental duty
- Corrosion resistant hardware
- Each unit shall have one (1) supply air collars, sized 20" round and are welded to the exterior wall.
- Each unit shall have one (1) return air collars, sized 20" round and are welded to the exterior wall.
- Integrated duct clamps on each 20" inlet / outlet
- Integrated casters
- 3rd party listed by ETL for both USA and Canada

150 kW Industrial Air Heater Functions:


- Single point 480V / 3PH / 60HZ power application power connection utilizing four (4) Cam-Lock power cables
- Panel mounted high voltage disconnect
- Main power on indicator light (green)
- Phase monitor and phase fail indicator light (red)
- Master On / Off switch
- Air flow differential pressure safety switch
- Heater safety control circuit and limits
- Micro processer temperature controller
- Entering and leaving air temperature control capability
- Over temperature pilot light
- Four (4) amber pilot light for heat stages energized



150 KW INDUSTRIAL AIR HEATER

Unit Performance / Data

Operating Performance



Fan Performance

Motor	10 HP
Motor Type	TEFC
Drive Configuration	Direct
Variable Speed	Yes

Equipment specifications are based manufactures published data; capacity may vary based upon field conditions