

ID	Pressure Rating	Vacuum Rating	Centerline Bend Radius	Compression	Weight per Ft.
(in.)	Psi	(Neg. in/Hg)	(in.)	(Approx. % of length at rest)	(lbs.)
12	9	3	10.3	40	2.08
16	6	2	16.8	40	3.25
18	4	1	17.3	35	3.52
20	3	1	17.9	33	4.15
24	1	1/2	21.2	20	5.08

**HI-TECH
DURAVENT**
Flexible Hose & Ducting

2PV-HM

Physical Characteristics, Pressure & Flex Values

Construction: Two ply polyester vinyl laminated with a spring steel wire helix as support and a hot melt external wear strip

Flame Resistant: UL94-V0

Wire Pitch: 12" = 1.25", 16" and up = 1.5"

Wire Gauge: 12" = .105, 16" and up = .135

Weight fabric: 9 oz.

Temperature range: -20° F to 180° F (intermittent to +225° F)

smiths 528 Carwellyn Road, Abbeville, SC 29620 • 1177 Markley Drive, Plymouth, IN 46563 • Tel: 800-348-6500
12" to 24" inside diameter
4610 Eastgate Parkway, Unit 3, Mississauga, Ontario, Canada L4W 3W6 • Tel: 905-602-9660 • Fax:

Standard color: 800-348-6500 Black hose with black wear strip, custom colors possible